



POLYPROPYLENE MINERAL
REINFORCED PP-MD SILENT AND
ULTRA SILENT PIPE SYSTEMS
Product Catalogue



almona SEWAGE & DRAINAGE



Only products bearing the NSF, SASO, WRAS, DVGW and SKZ Mark are certified by those organizations.

almonaplast.com

ABOUT US

Almona is a leading Saudi Arabian plastic pipe manufacturing company and since our establishment in 2008 we have constantly evolved to meet the requirements of our most demanding customers. Our aim is to provide sophisticated and diverse pipe solutions for hot and cold water applications, telecommunication networks, sewage and drainage systems together with water and gas infrastructure.

We are a certified to ISO 9001:2015 Quality Management Systems organization and all our products comply with the appropriate Saudi (SASO), German (DIN) and International (ISO) Standards. Our pipe systems for drinking water applications are NSF-61, WRAS and DVGW certified and all Almona products are tested extensively in our state-of-the-art laboratory, to ensure that the quality and performance are continuously maintained.

Almona's success is the result of the company's persistent commitment to continuous innovation and investment in technology, in the relentless pursuit of providing quality products and services. Today, we are pleased to offer a wide range of plastic products, divided into four categories:



BUILDINGS



SEWAGE AND DRAINAGE



INFRASTRUCTURE



TELECOMMUNICATION DUCTING

// WE DESIGN, DEVELOP, MANUFACTURE AND PROVIDE INNOVATIVE PIPE SOLUTIONS THAT BEST MEET THE NEEDS OF OUR CUSTOMERS //


CHARACTERISTICS OF **almona** PP-MD ULTRA SILENT PIPE SYSTEMS

Material	PP-MD mineral reinforced ultra silent pipe and fittings
Installation	Underground, inside and outside buildings
Area of applications	Drainage pipes in buildings and above ground installation <ul style="list-style-type: none">• Inside buildings (B) : DN40 to DN50• Inside and under the buildings (BD) : ≥DN 75
Colors	External and inner layers:  RAL 5012 Middle layer:  Light Blue
Noise Transmission Level	silent pipe: 0.5 l/s 10 dB; 1.0 l/s 12 dB; 2.0 l/s 12 dB; 4.0 l/s 14 dB ultra silent pipe: 0.5 l/s 14 dB; 1.0 l/s 16 dB; 2.0 l/s 16 dB; 4.0 l/s 18 dB
Ring Stiffness	> 6kN/m ²
Fire Behaviour	<ul style="list-style-type: none">• B2 (normally inflammable) DIN 4102-1• E (normally inflammable) EN 13501-1
Pipe Technology	3-layers technology <ul style="list-style-type: none">• Outer layer: High stiffness & impact resistant PP• Middle layer: High stiffness mineral reinforced soundproof• Inner layer: Chemical & abrasion resistant PP
Connection	Rubber ring joint socket with factory-installed 3 lip innovative sealing gasket
Gasket Technology	3-lips innovative design of rubber sealing gasket. <ul style="list-style-type: none">• Tensioning and retaining lip prevent dirt build-up between the pipe wall and the rubber gasket and stop the rubber gasket from being pressed out or rolling during push fit connection.• Wiping lip keep back any dirt on the pipe during the connection.• Sealing lip assures a thing long-term connection.
Options	UV resistant

ADVANTAGES OF almona PP-MD SYSTEMS




Ultra-Silent
Noise transmission level of 18 dB at a water flow of 2/l/s




High stiffness
due to 3-layer almona technology




Easy connection to other pipe systems such as PP-MD, HDPE, PVC without additional transition fittings required



High temperature resistance up to 90°C (peak 95°C)



Operation and installation at low temperatures (-25°C)



Resistance to external loads due to improved elasticity




Resistant to ground movement due to innovative 3-lip design of rubber sealing gasket



Leak free system due to 3-lip innovative rubber sealing gasket



Fast and easy installation (push-fit) and contamination free due to the innovative design of the rubber sealing gasket



Chemical resistance ranging from pH2 to pH12



Corrosion free system



100% recyclable and sustainable systems


PRODUCT RANGE

Pipes

Almona mineral reinforced silent and ultra silent polypropylene pipes range in size from DN 32mm to 200mm.

Silent PP-MD pipes with push-fit socket and 3-lip rubber sealing ring

Material: mineral reinforced polypropylene




Code	Noise Transmission Level* dB	DN (mm)	D (mm)	S (mm)	t (m)	Pipe length (m)
	12	32	45	3.4	42	6
	12	40	55	3.4	44	6
	12	50	65	3.4	46	6
	12	75	90	3.4	49	6
	12	90	107	3.4	54	6
	12	110	130	3.4	65	6
	12	125	149	3.9	72	6
	12	160	186	4.9	75	6
	12	200	228	6.2	108	6

*at a water flow of 2l/s

Ultra silent PP-MD pipes with push-fit socket and 3-lip rubber sealing ring

Material: mineral reinforced polypropylene




Code	Noise Transmission Level* dB	DN (mm)	D (mm)	S (mm)	t (m)	Pipe length (m)
	16	32	45	3.4	42	6
	16	40	55	3.4	44	6
	16	50	65	3.4	46	6
	16	75	90	3.4	49	6
	16	90	107	3.4	54	6
	16	110	130	4.2	65	6
	16	125	149	4.8	72	6
	16	160	186	6.2	75	6
	16	200	228	7.7	108	6

*at a water flow of 2l/s

Fittings


Almona mineral reinforced ultra silent polypropylene fittings range in size from DN 32mm to 200mm.

Bend 87,5°




Code	DN (mm)	L (mm)	Z1 (mm)	Z2 (mm)
	50	97	39	52
	75	125	60	69
	110	158	82	93
	160	195	95	108

Bend 45°




Code	DN (mm)	L (mm)	Z1 (mm)	Z2 (mm)
	50	75	17	27
	75	86	21	33
	110	110	34	41
	160	149	49	59

Reducer




Code	DN 1 (mm)	DN 2 (mm)	L (mm)	t (mm)	Z (mm)
	32	50			
	50	75			
	50	110			
	75	110			
	110	160	44	69	151

Double Socket




Code	DN (mm)	L (mm)	t (mm)	Z (mm)
	50	65	20	3
	75	75	22	3
	110	85	28	3
	160	108	38	4

Tee 87,5°




Code	DN 1 (mm)	DN 2 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
	50	50	38	40	83	136
	75	75	60	54	105	179
	110	110	82	73	134	231
	160	110	72	78	136	250
	160	160	95	103	155	298

Branch 45°




Code	DN 1 (mm)	DN 2 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
	50	50	16	68	68	142
	75	75	26	98	98	189
	110	110	34	141	141	251
	160	110	19	171	175	290
	160	160	53	205	205	358

Double Branch 45°




Code	DN 1 (mm)	DN 2 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
	110	110	34	141	141	320

Double Branch 87.5°



Code	DN 1 (mm)	DN 2 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
	110	110	82	73	93	300

End Cap



Code	DN (mm)	L (mm)
	110	50
	160	70

ACOUSTIC PERFORMANCE MEASUREMENTS

Determination of the acoustic performance of Almona PP-MD ultra-silent pipes and fittings systems was done in accordance to EN14366 "Laboratory measurement of noise from wastewater installations" and by following the German standards: DIN 4109, VDI 4100 and EN ISO 10052.

Almona PP-MD silent pipes and fittings system are certified at a noise transmission level of:

- 14 db at a water flow of 4l/s
- 12 db at a water flow of 2l/s
- 12 db at a water flow of 1l/s
- 10 db at a water flow of 0.5l/s

Almona PP-MD ultra-silent pipes and fittings system are certified at a noise transmission level of:


- 18 dB at a water flow of 4 l/s
- 16 dB at a water flow of 2 l/s
- 14 dB at a water flow of 0,5 l/s

The 12 and 16 dB values are measured at the bottom floor in the room next to the downpipe where the soil & waste flow and resulting noise levels are highest, especially in multi-storey living apartments or high-rise buildings that have a combined soil and waste flow.

All tests were carried out in the accredited institute, for building physics, Fraunhofer in Germany.



Schematic installation of the waste water system at the test facility





Saudi made

صنع بالسعودية



High quality

جودة عالية



almonaplast.com



T +966 11 410 2326
E info@almonaplast.com

P.O. Box: 270736 Riyadh 11352
Kingdom of Saudi Arabia

شركة مصنع المنى للمنتجات البلاستيكية
Almona Plastic Products Ltd. Co.